



# MAXIMIZE UPTIME

## Spend Time and Money on Your Business, Not on Roadside Repair

**How much will you save?** Go to [PrestoneCommand.com](http://PrestoneCommand.com) for the **UPTIME CALCULATOR**

FLEET MAINTENANCE COST	FLEET MAINTENANCE COST	FLEET MAINTENANCE COST	FLEET MAINTENANCE COST
when you use <b>COMMAND® COR-GUARD®</b> Nitrite Free (Red) Antifreeze + Coolant for 1,000,000 miles	when you use <b>ESI Precharged</b> (Purple) for 1,000,000 miles	when you use <b>COMMAND® COR-GUARD®</b> Nitrite Free (Red) Antifreeze + Coolant for 1,000,000 miles	when you use <b>Low Silicate Conventional</b> (Green) for 1,000,000 miles
<b>\$113,464.44</b>	<b>\$196,252.50</b>	<b>\$113,464.44</b>	<b>\$264,617.50</b>
<b>Cor-Guard® saves you \$82,788.06</b>		<b>Cor-Guard® saves you \$151,153.06</b>	

\*Calculations based on simulated data for this brochure and may not be entirely accurate. Visit [PrestoneCommand.com](http://PrestoneCommand.com) for the full Uptime Calculator

## Prestone® COMMAND® Heavy Duty Cor-Guard® Antifreeze+Coolant

### Nitrite Free Cor-Guard® Inhibitors Extended Life Antifreeze+Coolant

- Cor-Guard® increases uptime by instantly stopping the spread of rust, corrosion, pitting, gunk, grime, and buildup.
- Formulated for use in all Heavy and Light Duty engines
- Eliminates the need to add supplemental coolant additives
- Service Life 1,000,000 miles/20,000 hours\* - Heavy Duty applications only
- Works with all metals, rubber, elastomers, & seals

For Use In: Heavy & Light Duty Vehicles Classes 1-8

Compatibility: NF Non-2EH, NF-OAT

SKU	Pack	UPC	Meets or Exceeds OEM Performance Requirements	
<b>CONCENTRATE</b>			Cummins CES 14603	Volvo
AFC13000	6/1 gal.	7 97496 88112 0	Cummins Bulletin 3886132	Mack
AFC13000-55	55 gal. drum	7 97496 88126 7	Detroit Diesel 93K217	Freightliner
AFC13000-1KL	264 gal. tote	7 97496 88127 4	CAT EC-1	Paccar CS 0185
			Navistar CEMS B-1, Type IIIA	Peterbilt
<b>50/50</b>			International	Kenworth
AFC13100	6/1 gal.	7 97496 88114 4	John Deere H24	Komatsu
AFC13100-55	55 gal. drum	7 97496 88128 1	John Deere H24 C1	Komatsu KES 07.892
AFC13100-1KL	264 gal. tote	7 97496 88129 8	John Deere JDS-G135	Kubota
			Ford WSS-M97-B44D	GM Heavy Truck
			GM 6277M	Chrysler/Dodge/Ram
			GMW 34290	Ford WSS-M97B57-A1/A2
			<b>Meets or Exceeds Industry &amp; Governmental Standards:</b>	
			ASTM D6210	TMC RP338A
			ASTM D3306	TMC RP364
			ASTM D4985	TMC RP351
			ASTM D7583	JIS K2234
			ASTM D4340	SAE J1034
			SAE J1941	



\* Class 8 wet sleeve liner applications. With a complete flush/drain and fill per manufacturer's recommendations. Always refer to the vehicle manufacturer owner's or service manual for the recommended change intervals, cooling system capacity, and specific cooling system service instructions. PRESTONE®, COMMAND®, and COR-GUARD® are registered trademarks of Prestone Products Corporation. All other marks are those of their respective owners.

# Formulated for Heavy Duty Engines

**Prestone**  
Superior Technology

**Prestone COR-GUARD**

with Prestone

VS

Ordinary Coolant  
Corrosion & Pitting

with Ordinary

**300 HOUR**  
ASTM Water Pump High Stress Test

PROPERLY MAINTAIN YOUR COOLING SYSTEM		COMMAND® COR-GUARD® Nitrite Free (Red)	COMMAND® Nitrite Free ELC (Yellow)	COMMAND® Nitrited ELC (Red)	COMMAND® ESI Precharged (Purple)
<b>Class 8</b> 33,001+ CEMENT TRUCK TRUCK TRACTOR DUMP TRUCK SLEEPER CAB					
<b>Class 7</b> 26,001 to 33,000 lbs CITY TRANSIT BUS TRUCK TRACTOR REFUSE FURNITURE		Works with ALL Vehicles	Works with ALL Vehicles	Works with Class 6-8	Works with Class 6-8
<b>Class 6</b> 19,501 to 26,000 lbs BEVERAGE TRUCK RACK TRUCK SINGLE-AXLE SCHOOL BUS					
<b>Class 5</b> 16,001 to 19,500 lbs LARGE WALK-IN CITY DELIVERY BUCKET TRUCK					
<b>Class 4</b> 14,001 to 16,000 lbs CITY DELIVERY BOX TRUCK LARGE WALK-IN					
<b>Class 3</b> 10,001 to 14,000 lbs HEAVY-DUTY PICKUP BOX TRUCK CITY DELIVERY WALK-IN					
<b>Class 2</b> 6,001 to 10,000 lbs CARGO VAN FULL-SIZE PICKUP STEP VAN MINIVAN					
<b>Class 1</b> 6,000 lbs or less MINIVAN CARGO VAN SUV MINIVAN					

## Prestone® COMMAND® Heavy Duty Nitrite Free Antifreeze+Coolant



### Nitrite Free Extended Life

- Formulated for use in all Heavy and Light Duty engines
- Nitrite Free formula provides excellent protection for aluminum and all other engine metals
- Protects against liner pitting and corrosion protections
- Service Life 750,000 miles/15,000 hours\* - Heavy Duty applications only
- Eliminates the need to add supplemental coolant additives
- Works with all NF-OAT coolants

For Use In: Heavy & Light Duty Vehicles Classes 1-8  
Compatibility: NF-OAT

SKU	Pack	UPC
<b>CONCENTRATE</b>		
AFC12000	6/1 gal.	7 97496 87906 6
AFC12000-55	55 gal. drum	7 97496 87908 0
AFC12000-1KL	264 gal. tote	7 97496 87909 7
<b>50/50</b>		
AFC12100	6/1 gal.	7 97496 87910 3
AFC12100-55	55 gal. drum	7 97496 87912 7
AFC12100-1KL	264 gal. tote	7 97496 87913 4

### OEM Approvals/Registrations

This product meets Cummins® Eng. Std. CES14439  
Detroit Diesel 93K217

### Meets or Exceeds OEM Performance Requirements

CAT EC-1  
Navistar CEMS B-1, Type IIIA  
International  
Volvo  
Mack  
John Deere H24  
John Deere H24 C1  
John Deere JDS-G135

Freightliner  
Paccar  
Paccar CS 0185  
Peterbilt  
Kenworth  
GM 6277M  
GMW 34290  
Ford WSS-M97-B44D

### Meets or Exceeds Industry & Governmental Standards:

ASTM D6210  
ASTM D3306  
ASTM D4985  
ASTM D7583  
ASTM D4340  
SAE J1941

TMC RP338A  
TMC RP364  
TMC RP351  
JIS K2234  
SAE J1034

## Prestone® COMMAND® Heavy Duty Extended Life Antifreeze+Coolant



### Nitrited Extended Life

- Formulated for Heavy Duty Vehicles
- Nitrited formula provides excellent protection for aluminum and all other engine metals
- Protects against liner pitting and corrosion protections.
- Complete liner pitting & corrosion protection
- Service Life 750,000 miles/15,000 hours\* with use of extender at 300,000 miles/6,000 hours and 600,000 miles/12,000 hours - Heavy Duty applications only

For Use In: Heavy Duty Vehicles Classes 6-8.  
Compatibility: NOAT

SKU	Pack	UPC
<b>CONCENTRATE</b>		
AFC11000	6/1 gal.	7 97496 87757 4
AFC11000-55	55 gal. drum	7 97496 87758 1
AFC11000-1KL	264 gal. tote	7 97496 87759 8
<b>50/50</b>		
AFC11100	6/1 gal.	7 97496 87761 1
AFC11100-55	55 gal. drum	7 97496 87762 8
AFC11100-1KL	264 gal. tote	7 97496 87763 5

### OEM Approvals/Registrations

This product meets Cummins® Eng. Std. CES14439  
Detroit Diesel 93K217

### Meets or Exceeds OEM Performance Requirements

CAT EC-1  
Navistar CEMS B-1, Type III  
International  
Volvo  
Mack  
Freightliner  
John Deere JDS-G135

Paccar  
Kenworth  
Peterbilt  
New Holland  
Waukesha  
John Deere H24  
John Deere H24 C1

### Meets or Exceeds Industry & Governmental Standards:

ASTM D6210  
ASTM D3306  
ASTM D4985  
ASTM D4340  
SAE J1941

TMC RP329A  
TMC RP338A  
TMC RP364  
TMC RP351  
SAE J1034

## Prestone® COMMAND® Heavy Duty ESI Antifreeze+Coolant



### Extended Service Interval - ESI

- Formulated for Heavy Duty Vehicles
- Compatible with any IAT antifreeze/coolant
- Nitrited, pre-charged with supplemental coolant additives
- Extended service interval; fully formulated to provide engine protection
- Stabilized, low silicate (no phosphates) formula helps reduce deposits & reduce hard water scale buildup
- Requires monitoring & maintaining additive levels

For Use In: Heavy Duty Vehicles Classes 6-8  
Compatibility: ESI & IAT

SKU	Pack	UPC
<b>CONCENTRATE</b>		
AFC10000	6/1 gal.	7 97496 87765 9
AFC10000-55	55 gal. drum	7 97496 87766 6
AFC10000-1KL	264 gal. tote	7 97496 87767 3
<b>50/50</b>		
AFC10100	6/1 gal.	7 97496 87769 7
AFC10100-55	55 gal. drum	7 97496 87770 3
AFC10100-1KL	264 gal. tote	7 97496 87771 1

### OEM Approvals/Registrations

This product meets Cummins® Eng. Std. CES14439  
Detroit Diesel 93K217

### Meets or Exceeds OEM Performance Requirements

Cummins CES 9078-4  
Detroit Diesel 75E298  
Navistar CEMS B-1, Type II  
Mack 014617004  
Freightliner 48-25961  
Freightliner 48-25878

Freightliner 48-22880  
Kenworth R026-170-97  
Peterbilt 8502.002  
John Deere H24, H24 A1  
John Deere JDS-G135  
John Deere 8650-5

### Meets or Exceeds Industry & Governmental Standards:

ASTM D6210  
ASTM D3306  
ASTM D4985  
ASTM D4340  
GCA A-A-52624  
CID A-A-52624A

TMC RP329A  
TMC RP338A  
TMC RP351  
SAE J1034  
SAE J1941