



Heavy Duty NITRITED

EXTENDED LIFE COOLANT



Learn More about our technology on the back

CAT EC-1 Compatible
Cummins® Certified - CES 14439
 See all OEM listings below

- ✓ **Protects Against Rust & Corrosion**
- ✓ **750,000 Mile Fluid Guarantee***
 When extender added at 300,000 & 600,000 miles
- ✓ **For use in:**
 - Heavy & Medium Duty Vehicles - Classes 6-8
 - Aluminum & Cast Iron Components
 - Diesel Engines & Natural Gas Engines

Meets or Exceeds OEM Performance Requirements:	
CAT EC-1	Paccar
Cummins CES 14439	Kenworth
International	Peterbilt
Volvo	New Holland
Mack	Waukesha
Freightliner	John Deere H24/H24 C1
Navistar CEMS B-1, Type III	John Deere JDS-G135

Meets or Exceeds Industry & Governmental Standards:			
ASTM D6210	ASTM D4340	TMC RP364	SAE J1034
ASTM D3306	TMC RP329A	TMC RP351	SAE J1941
ASTM D4985	TMC RP338A		

*Fluid service life guaranteed up to earlier of 750,000 mi. or 15,000 hrs. Follow steps to achieve service life: (1) Perform cooling system flush, then fill cooling system with proper mixture of PRESTONE COMMAND® Nitrited ELC Concentrate and high quality water. (2) Top off coolant levels as necessary using only PRESTONE COMMAND® Nitrited ELC Prediluted. (3) Test coolant every 6,000 hrs or 1 yr intervals using refractometer to test correct coolant/water mixture and using test strips to assess nitrite level and pH. (4) Add PRESTONE COMMAND® Nitrited ELC Prediluted or a NOAT coolant extender in accordance with OEM recommendations at 300,000 mi and 600,000 mi and as necessary to maintain nitrite level and pH. (5) Use new coolant if replacing a cooling system part. Guarantee may be subject to other terms and conditions – please visit Prestone.com or call 1-888-269-0750 for further information. PRESTONE COMMAND® is a registered trademark of Prestone Products Corporation. All other marks are those of their respective owners.



Heavy Duty NITRITED EXTENDED LIFE COOLANT

CONCENTRATE	PACK	UPC
AFC11000	6/1 gal.	7 97496-87757 4
AFC11000-55	55 gal. drum	7 97496-87758 1
AFC11000-1KL	264 gal. tote	7 97496-87759 8

READY TO USE	PACK	UPC
AFC11100	6/1 gal.	7 97496-87761 1
AFC11100-55	55 gal. drum	7 97496-87762 8
AFC11100-1KL	264 gal. tote	7 97496-87763 5

AFC11000 TECHNICAL DATA

Composition by Weight	Typical Values
Antifreeze/Coolant Concentrate:	96.7%
Total Water:	3.3%
Dyes:	Trace

Properties	Typical Values	Tests
Color:	Red	
Odor:	Characteristic	
Ash Content:	1.9% by weight	ASTM D1119
pH at 50 vol%:	8.2-8.8	ASTM D1287
Reserve Alkalinity:	5.5 mL	ASTM D1121
Density at 15°C, g/mL:	1.1185	ASTM D1122
Freezing Point at 50 vol%:	-34°F (-37°C)	ASTM D1177
Boiling Point at 50 vol%: <i>Under standard pressure</i>	+226°F (+108°C)	ASTM D1120
Foam Test:	51 mL/1.4 sec.	ASTM D1881

AFC11100 TECHNICAL DATA

Composition by Weight	Typical Values
Antifreeze/Coolant Concentrate:	52.5%
Total Water:	47.5 %
Dyes:	Trace

Properties	Typical Values	Tests
Color:	Red	
Odor:	Characteristic	
Ash Content:	1.0% by weight	ASTM D1119
pH:	8.2-8.8	ASTM D1287
Reserve Alkalinity:	2.7 mL	ASTM D1121
Density at 15°C, g/mL:	1.0743	ASTM D1122
Freezing Point:	-34°F (-37°C)	ASTM D1177
Boiling Point: <i>Under standard pressure</i>	+226°F (+108°C)	ASTM D1120
Foam Test:	51 mL/1.4 sec.	ASTM D1881

Most of our PRESTONE COMMAND® Antifreeze+Coolant Products come in 55 Gal. Drums, 264 Gal. Totes and Bulk.



55 gal. drum

264 gal. tote